

PowerTile-CS5000H-X-P

低压堆栈式储能电源（并离网）

昆宇电源
COSPOWERS



- 1 家居化风格，优雅美观
- 2 多种工作模式（光伏优先、市电优先、逆变优先）
- 3 简易安装和维护，即插即用
- 4 自带ISO/Android.App监控
- 5 单个电池5.12kWh，可扩展至20.48KWh
- 6 多重保护及告警系统，安全可靠

参数/型号		CS5000H-5-P	CS5000H-10-P	CS5000H-15-P	CS5000H-20-P
逆变输出	额定输出功率	5500W			
	最大峰值功率	11000VA			
	额定输出电压	230Vac 单相			
	频率	50/60±0.3Hz			
	切换时间	10ms			
PV输入参数	MPPT数量	2			
	PV开路电压	500/500V			
	最大输入功率	4000+4000V			
	MPPT电压范围	120~450Vdc			
	最大PV输入电流	16/16A			
	最大短路电流	27/27A			
市电/发电机输入	输入电压范围	90~280Vac			
	输入频率范围	50/60Hz			
	最大旁路电流	40A			
电池参数	电池类型	磷酸铁锂			
	电池额定电压	51.2V			
	电压范围	44.8~57.6V			
	电池电量	5.12kWh	10.24kWh	15.36kWh	20.48kWh
	最大充/放电倍率	0.5/1C			
工作条件	充电温度范围	5~55°C			
	放电温度范围	-15~60°C			
	湿度	5~95%			
	散热方式	风冷			
	重量	107Kg	157Kg	207Kg	257Kg
	尺寸 (W*D*H)	725*515*445mm	725*515*585mm	725*515*725mm	725*515*865mm
	通讯方式	WIFI/RS485			
其它参数	认证	IEC62619、IEC62109、CE-EMC			



深圳昆宇电源科技有限公司

网址:WWW.COSPOWERS.COM

地址:深圳市宝安区燕罗街道罗田社区第三工业区广田路2号

电话:0755-33185898

版权及最终解释权归深圳昆宇电源科技有限公司所有

PowerTile-CS5000H-X-P

Low-Voltage Stackable Energy Storage Power Supply (Grid-Tied & Off-Grid)



- 1 Homestyle design, elegant and beautiful
- 2 Multiple working modes (solar priority, utility priority, inverter priority)
- 3 Easy installation and maintenance, plug and play
- 4 Possess ISO/Android. App to monitor
- 5 Single battery 5.12kWh, expandable up to 20.48kWh
- 6 Multiple protection and alarm system, safe and reliable

Parameters/ Model		CS5000H-5-P	CS5000H-10-P	CS5000H-15-P	CS5000H-20-P
Inverter Output	Rated Output Power	5500W			
	Maximum Peak Power	11000VA			
	Rated Output Voltage	230Vac Single Phase			
	Frequency	50/60±0.3Hz			
	Transfer Time	10ms			
PV Input Parameters	Number of MPPTs	2			
	PV Open Circuit Voltage	500/500V			
	Maximum Input Power	4000+4000V			
	MPPT Voltage Range	120~450Vdc			
	Maximum PV Input Current	16/16A			
	Maximum Short-Circuit Current	27/27A			
Utility/Generator Input	Input Voltage Range	90~280Vac			
	Input Frequency Range	50/60Hz			
	Maximum Bypass Current	40A			
Battery Parameters	Battery Type	LFP			
	Battery Rated Voltage	51.2V			
	Voltage Range	44.8~57.6V			
	Battery Energy Capacity	5.12kWh	10.24kWh	15.36kWh	20.48kWh
	Maximum Charge/Discharge Rate	0.5/1C			
Operating Conditions	Charge Temperature Range	5~55°C			
	Discharge Temperature Range	-15~60°C			
	Humidity	5~95%			
	Cooling Method	Air Cooling			
	Weight	107Kg	157Kg	207Kg	257Kg
	Dimensions (W*D*H)	725*515*445mm	725*515*585mm	725*515*725mm	725*515*865mm
	Communication Interface	WIFI/RS485			
Other Parameters	Certifications	IEC62619、IEC62109、CE-EMC			



Shenzhen Coslight Power Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.2, Guangtian Road, No.3 Industrial Zone, Luotian Community, Yanluo Street, Baoan District, Shenzhen, Guangdong Province, P.R.C

T: +86-755-33185898

Copyright and final interpretation rights belong to Shenzhen Coslight Power Technology Co., Ltd.